

Down Light IP44



3 inch

4 inch

6 inch

8 inch

MODEL NO.:	GLR-8010	GLR-8020	GLR-8030	GLR-8040
SKU CODE:	8011 3000K Warm White 8012 4500K Daylight White 8013 6000K Cool White	8021 3000K Warm White 8022 4500K Daylight White 8023 6000K Cool White	8031 3000K Warm White 8032 4500K Daylight White 8033 6000K Cool White	8041 3000K Warm White 8042 4500K Daylight White 8043 6000K Cool White
WATTS:	12W	15W	25W	30W
TYPE:	Recessed Down Light	Recessed Down Light	Recessed Down Light	Recessed Down Light
Voltage:	AC 100 - 240 V	AC 100 - 240 V	AC 100 - 240 V	AC 100 - 240 V
Lumen:	950Lm	1200Lm	2100Lm	2450Lm
CRI:	Ra>80	Ra>80	Ra>80	Ra>80
Angle:	120°	120°	120°	120°
Material:	PC/Aluminium	PC/Aluminium	PC/Aluminium	PC/Aluminium
Chip Type:	Epistar	Epistar	Epistar	Epistar
PF:	0.5 / 0.9	0.5 / 0.9	0.5 / 0.9	0.5 / 0.9
Operating Temp:	-20~+45°C	-20~+45°C	-20~+45°C	-20~+45°C
Life Span:	35,000 H	35,000 H	35,000 H	35,000 H
Dimension (AxB):	Φ110x45mm	Φ140x45mm	Φ190x45mm	Φ228x45mm
Cut out (C)	100mm	130mm	170mm	200mm

